

CloudEngine 9860-4C-El-A-G Data Center Switch





Product Overview

The CloudEngine 9860-4C-EI-A-G series is a new generation of high-performance, high-density, low-latency Ethernet flexible card switches for data centers. The CloudEngine 9860-4C-EI-A-G series adopts advanced hardware design and provides high-density 400GE/100GE/40GE ports to support rich data center features.

The CloudEngine 9860-4C-EI-A-G series switches are positioned at the core or aggregation of data centers, helping enterprises and operators build a data center network platform for the cloud computing era, and can also be used for the core or aggregation of campus networks.



Technical Specification

Items	CloudEngine 9860-4C-EI-A-G
Port Description	4 slots for up to 128 100GE QSFP28 or 32 400GE QSFP-DD
Switching Capacity	25.6Tbps
Packet Forwarding Rate	8000Mpps
Air Duct Type	Standard rear front air duct
$\begin{array}{c} \text{Chassis Dimensions} \\ (W \times D \times H) \end{array}$	442mm × 765mm × 175mm
Full Weight	43.2kg (including 4 Psus, 4 fan modules and 4 cards) 33.04kg (including 4 power modules and 4 fan modules)
	Working temperature: 0°C to 40°C (0m to 1800m)
Environmental Requirements	Storage Temperature: -40°C to +70°C Relative Humidity: 5% to 95%RH, non-condensing
Rated Input Voltage	1200W AC and 240VDC power module Rated Input Voltage range: AC: 100VAC to 240VAC. 50/60Hz, DC: 240VDC 1200W DC power module: -48C DC: -48VDC to -60VDC; +48VDC: +48VDC
Input Voltage Range	1200W AC &240VDC power module: AC: 90VAC to 290VAC, 45Hz-65Hz; DC: 190VDC to 290VDC 1200W DC power module: -48VDC: -38.4VDC to -72VDC; +48VDC: +38.4VDC to +60VDC
Typical Power Consumption	Four CE98-D32CQ cards fully configured: 1291W Four CE98-D8DQ cards: 953W

■ Full Range of CE9000 Models

Model	CloudEngine 9800-G: High-density 100GE Card Switch
CloudEngine 9860-4C-EI-A-G	CE9860-4C-EI-A-G Host (4*sub-card slots,4*AC power supply,4*fan box,4*32 port 100GE QSFP28 interface card, port side air intake)
CloudEngine 9855-32DQ-G	CE9855-32DQ-B-G Switch (32*400GE QSFP-DD,2*AC power supply,6*fan box, port side air intake)

Model	CloudEngine XH9100-G Series Data Center Switches
CloudEngine XH9110-24BQ8DQ-G	XH9110-24BQ8DQ-B-G Switch (24*200GE QSFP56,8*400GE QSFP-DD,2*AC power supply,5*fan box, port side air intake)



Ignite future, connect world



Guangdong Glory Technology Co., Ltd.

Email: service@glory-t.tech Hotline: +86 400-800-6805

For more information, please visit www.glory-t.cn

*The descriptions and information displayed in the product promotional materials are for reference only. The actual delivered product shall prevail. The final interpretation right belongs to GLORY.